

0.9mm ST Optical Fiber Pigtail

Pigtail is used to connect optical fiber and optical fiber coupler, It includes connector and an optical fiber. it is another form of patch cord, and a connector which similar to half of patch cord. Used in the ending part of optical communication, and connected to the optical devices. Or the connection transmission equipment and ODF frame, etc

Features

- 1/2/4/8/12/24 Fiber counts are available
- OS2/OM1/OM2/OM3/OM4/OM5 Fiber types are available
- 900um LSZH/PVC/Hytrel Jacket types are available
- ROHS compliant
- •IEC61300/IEC61753/TIA455/IEC60793/IEC60794/IEC61755 compliant

Applications

- Local Area Networks (LANs)
- Data processing networks
- Instrument
- Premise installations

Specifications

Q	KOC 嘉万光通信	

Item	Specification		
	Single Mode	Multimode	
Insertion Loss	≤0.3dB	≤0.3dB	
Return Loss	≥50dB(PC), ≥60dB(APC)	≥30dB	
Repeatability	≤0.2	≤0.2	
Durability	≤0.2 dB typical change, 500 matings	≤0.2 dB typical change, 500 matings	
Interchangeability	≤0.2dB	≤0.2dB	
Tensile Strength	>10N	>10N	
Operating Temperature	-20°C ~ 70°C	-20°C ~ 70°C	