



## Specification

### 2.0mm LC Connector

2.0mm LC connectors usually are used for patchcord. And the connectors have many types can be choosed, for example: APC or UPC ferrule, blue or green hosuing, standard or specifical boot...

#### Features

- High precision alignment
- Precision anti-rotation key and corrosion resistant body
- Good insertion loss and back reflection loss
- ROHS compliant
- TIA604-10&IEC61754-20 compliant

#### Application

- Gigabit Ethernet
- Video
- Multimedia
- Active device termination
- Premise installations
- Telecommunication networks

#### Standards

All components of/and the final product are designed and tested to conform the requirements of IEC 60874, Bellcore/Telcordia GR-326, EIA/TIA 604-10, IEC61754-20, EIA/TIA 568, IEC61300-2, IEC61300-3, IEC61753-1, EIA/TIA455.



Item	Single mode	Multi mode
Insertion Loss	≤0.3dB	≤0.3dB
Return Loss	APC≥60dB, PC≥50dB	PC≥30dB
Durability	≤0.2dB typical change, 1000 matings	≤0.2dB typical change, 1000 matings
Operating Temperature	-40°C ~ 85°C	-40°C ~ 85°C
Ferrule Hole Sizes	SM:125.0+1/-0μm, Concentricity: ≤1.0μm	
	SM:125.5+1/-0μm, Concentricity: ≤1.0μm	
	SM:126.0+1/-0μm, Concentricity: ≤1.0μm	
	MM:127.0+1/-0μm, Concentricity: ≤4.0μm	

#### Availability

- The connector can be supplied as a pre-assembled one-piece connector or as connectorkits.
- Housing kits without ferrule are available.
- LC/PC and LC/APC are available.